





# **Features and Benefits**

- · Sleek and compact design for standalone or wallmount
- Low power
- Drive bays for a 2.5" HDD & a Slim DVD ROM Combo
- I accessible CF card reader protected by the lid
- Accessible bottom door for easily upgrading So-DIMM memory
- Powered by I2V DC-in external adapter
- Support Intel® Core 2 Duo processors

### SYSTEM SPECIFICATIONS

- Dimensions (L x W x H): 230 mm x 181 mm x 50 mm Mounting: Standalone or Wall-Mounted

- · Construction: S.E.C.C.(Steel-Electrogalvanized-ColdRolled-Coil)
- · Net Weight: I.9kg

#### **DRIVE BAY**

• Expansion for a Slim 2.5" HDD and a Slim DVD-ROM Combo

#### **SYSTEM FAN**

- $\boldsymbol{\cdot}$  One CPU cooler, including head-sink and fan
- Dimensions (L x W x H): 50 mm x 50 mm x 22 mm

- · LED for power and HDD status
- · LED for LAN status

### **POWER ADAPTER**

- AC Input: 100 ~ 240 V; I.2A, 50-60Hz
- DC Output: 12 V / 6.25A (75W)

## **OPERATING TEMPERATURE**

· 0 to 45°C under 10-90%RH

## STORAGE TEMPERATURE

· -20 to 70°C under 5-95%RH

#### **EMC AND SAFETY**

· FCC class B, CE, UL, CUL (certification in progress)

### SYSTEM MODEL

#### SYSTEM MODEL


· ES100 (without CPU)



ES100 industrial main board inside, w/ 3.5" DFI-ACP SBC board - CT950-B inside Support Intel® Core 2 Duo, Core Duo, Solo and Celeron-M CPU by 478 socket and Intel® 945GME / ICH7M chipset. I CF slot, I Giga-LAN, I2V DC-In

# FRONT PANEL EXTERNAL I/O

# **REAR PANEL EXTERNAL I/O**



**ES100** 

# **Embedded Systems**

- **Packing List** · I x ES100 Unit
- · I x Power Adapter 75W \*
- · I x Utility Manual CD
- · I x Installation Guide
- · I x IDE cable
- · I x ES100 chassis kit
- · 2 x L-Shaped Brackets for wall-mounted
- · I x SATA Cable
- · I x SATA-Power Cable
- \* The power cord is ordered separately, based on the different areas requirements.

# **ORDERING INFORMATION**

· ES100 750-ES1001-000G ES100 Embedded System with 3.5" DFI SBC board - CT950-B, Support Intel® Core 2 Duo, Duo/Solo and Celeron-M CPU, Intel® 945GME / ICH7M, w/ Heat-Sink & 12V Fan,  $2 \times USB$ ,  $2 \times COM$ , I x LAN, I x CF Slot, I x DVD ROM Combo

# **OPTIONAL ITEMS**

· 635-508092-100G Slim HDD-SATA 2.5" 80GB 5400rpm

· 632-116020-400G Slim DVD-ROM Combo

· 332-700190-004G Power Cord US Type 1830mm RoHS


## **SPARE PARTS**

· 671-107501-000G Power Adapter 75W · 332-853044-004G IDE Cable 15cm · 332-753011-004G SATA Cable 12cm

· 332-853045-004G SATA-Power Cable · 685-ES1000-000G ES100 Metal Case

L-shaped bracket for wall-mounted · 551-862034-000G · 552-200039-000G CPU Cooler, 50x50x22mm, w/Fan 12V

# **DIMENSIONS**







Transportation







POS Application

General Application

All product names mentioned are trademarks or registered trademarks of their respective companies. All specifications are subject to change without prior notice. © DFI Inc.

Distribue par Anteor - www.anteor.com - Tel: 01 61 37 07 00