

## G4V600-BS

### Intel® 845GV Socket 478 ATX System Board

#### PROCESSOR

- Intel® Pentium® 4 (Prescott and Northwood) processor
  - Intel Hyper-Threading Technology
  - FSB: 400MHz and 533MHz
- Intel® Celeron® / Celeron® D processor
  - 400MHz system data bus
- Processor socket: Socket 478

#### CHIPSET

- Intel® chipset
  - Intel® 845GV Memory Controller Hub (MCH)
  - Intel® 82801DB I/O Controller Hub (ICH4)

#### SYSTEM MEMORY

- Two 184-pin DDR SDRAM DIMM sockets
- 2.5V unbuffered PC1600 (DDR200) or PC2100 (DDR266) DDR SDRAM DIMM
- Supports maximum of 2.1GB system memory using 64Mbit, 128Mbit, 256Mbit or 512Mbit technology
  - Double-sided x16 DDR SDRAM DIMM is not supported
- Supports ECC function

#### BIOS

- Award BIOS
- 4Mbit flash memory

#### ENERGY EFFICIENT DESIGN

- Supports ACPI specification and OS Directed Power Management
- Supports ACPI STR (Suspend to RAM) function
- Wake-On-Events include:
  - Wake-On-PS/2 Keyboard/Mouse
  - Wake-On-USB Keyboard
  - Wake-On-Ring (through internal or external modem)
  - Wake-On-LAN
  - RTC timer to power-on the system
- System power management supported
- CPU stopped clock control
- Hardware supports SMI green mode
- Microsoft®/Intel® APM 1.2 compliant
- Soft Power supported - ACPI v1.0b specification
- AC power failure recovery

#### DAMAGE FREE INTELLIGENCE

- Monitors CPU/system temperature and overheat alarm
- Monitors 5VSB/VBAT/1.5V/3.3V/±5V/±12V/Vcore voltages and failure alarm
- Monitors CPU/chassis/2nd fan speed and failure alarm
- Read back capability that displays temperature, voltage and fan speed
- Opened chassis alarm
- Watchdog timer function

#### ONBOARD AUDIO FEATURES

- 18-bit stereo full-duplex codec with independent variable sampling rate
- High quality differential CD input
- True stereo line level outputs
- S/PDIF-out interface
- 2-channel audio output

#### SERIAL ATA INTERFACE

- VIA VT6421L controller
- Supports two Serial ATA (SATA) interfaces which are compliant with SATA 1.0 specification (1.5Gbps interface)

#### PCI IDE INTERFACE

- Supports up to UltraDMA 100Mbps hard drives
- PIO Mode 4 Enhanced IDE (data transfer rate up to 14MB/sec.)

#### ONBOARD LAN FEATURES

- 82562 fast ethernet controller
- Basic 10/100 Client Connection. Supports 559 level cable and PHY Stats. Support for Server OS included as check item, but no Server function included
- Same Quality Driver suits as 82559
- Supports DMI/SNMP/WMI
- 10/100 Auto Sensing
- IEEE 802.3, 10BASE-T/100BASE-TX compliant physical layer interface
- IEEE 802.3u Auto-Negotiation
- 48-pin SSOP, 3.3V device

#### REAR PANEL I/O PORTS

- 1 mini-DIN-6 PS/2 mouse port
- 1 mini-DIN-6 PS/2 keyboard port
- 1 DB-25 parallel port
- 2 DB-9 serial ports
- 1 RJ45 LAN port
- 4 USB 2.0/1.1 ports
- Line-out, line-in and mic-in

#### I/O CONNECTORS

- 1 CompactFlash™ socket
- 1 connector for 2 additional external USB 2.0/1.1 ports
- 1 front audio connector for external line-out and mic-in jacks
- 2 internal audio connectors (CD-in and AUX-in)
- 1 S/PDIF-out connector
- 1 connector for IrDA interface
- 2 Serial ATA connectors
- 2 IDE connectors
- 1 floppy connector
- 1 20-pin ATX power connector
- 1 4-pin ATX 12V power connector
- 1 Wake-On-LAN connector
- 1 Wake-On-Ring connector
- 1 chassis open connector
- 1 keylock connector
- 1 front panel connector
- 3 fan connectors

#### EXPANSION SLOTS

- 7 PCI slots

#### COMPATIBILITY

- PCI 2.2 and AC '97 compliant

#### PCB

- 4 layers, ATX form factor
- 30.5cm (12") x 24.4cm (9.6")